

Appl. No. 10/649,335

Rule 312 Amdt. dated May 24, 2006

In Reply to Notice of Allowability of Feb. 24, 2006

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application.

1. (Previously Presented) A method of interference reduction in a spread spectrum receiver including a rake receiver having a plurality of fingers for processing a plurality of data signals and an associated plurality of pilot signals, the method comprising:

generating a plurality of intra-finger interference cancellation signals using said plurality of pilot signals, each of said plurality of intra-finger interference cancellation signals being associated with one of said plurality of fingers;

weighting ones of said plurality of intra-finger interference cancellation signals so as to generate a set of weighted intra-finger interference cancellation signals;

synthesizing at least one inter-finger interference cancellation signal in accordance with said set of weighted intra-finger interference cancellation signals;

receiving, by said plurality of fingers, said at least one inter-finger interference cancellation signal, wherein different ones of the plurality of fingers can receive different ones of said at least one inter-finger interference cancellation signal; and

subtracting said at least one inter-finger cancellation signal from one of said plurality of data signals.

2. (Previously Presented) The method of claim 1 wherein said plurality of fingers is comprised of N fingers, wherein N is an integer, and wherein said set is comprised of N-1 weighted intra-finger interference cancellation signals.

3. (Currently Amended) The method of claim 1 wherein said synthesizing further includes generating ~~said~~ a plurality of inter-finger interference cancellation signals respectively associated with said plurality of fingers, each of said inter-finger interference cancellation signals being synthesized in accordance with a different group of ones of said set of weighted

Appl. No. 10/649,335  
Rule 312 Amdt. dated May 24, 2006  
In Reply to Notice of Allowability of Feb. 24, 2006

intra-finger interference cancellation signals.

4. (Previously Presented) The method of claim 3 wherein said subtracting further includes subtracting each of said plurality of inter-finger interference cancellation signals from a corresponding one of said plurality of data signals, thereby yielding a plurality of interference-reduced data signals.

5. (Original) The method of claim 1 wherein said generating further includes creating a plurality of pilot channel models, each of said plurality of pilot channel models being associated with one of said plurality of fingers.

6. (Original) The method of claim 1 wherein said plurality of pilot signals is comprised of a plurality of primary pilot signals and a corresponding plurality of secondary pilot signals, said generating further including creating a plurality of primary pilot channel models corresponding to said plurality of primary pilot signals and a plurality of secondary pilot channel models corresponding to said plurality of secondary pilot signals.

7. (Previously Presented) The method of claim 5 wherein said generating includes generating a first of said plurality of intra-finger interference cancellation signals within a first of said plurality of fingers, said first of said plurality of intra-finger interference cancellation signals being created based at least in part upon a first of said plurality of pilot channel models associated with said first of said plurality of fingers.

8. (Previously Presented) The method of claim 4 wherein each of said intra-finger interference cancellation signals is generated based at least in part upon one of said plurality of interference-reduced data signals.

Appl. No. 10/649,335

Rule 312 Amdt. dated May 24, 2006

In Reply to Notice of Allowability of Feb. 24, 2006

9. (Currently Amended) A method of interference reduction in a spread spectrum receiver including a rake receiver having  $N$  fingers for processing  $N$  data signals and  $N$  associated pilot signals, wherein  $N$  is an integer, the method comprising:

generating  $N$  intra-finger interference cancellation signals using said  $N$  associated pilot signals, each of said  $N$  intra-finger interference cancellation signals being associated with one of said  $N$  fingers;

weighting ones of said  $N$  intra-finger interference cancellation signals so as to generate  $N$  weighted intra-finger interference cancellation signals;

synthesizing said  $N$  inter-finger interference cancellation signals, each of said  $N$  inter-finger interference cancellation signals being synthesized on the basis of one or more of said  $N$  weighted intra-finger interference cancellation signals; and

subtracting each of said  $N$  inter-finger interference cancellation signals from a corresponding one of said  $N$  data signals, thereby generating  $N$  interference-reduced data signals.

10. (Original) The method of claim 9 further including determining interference levels remaining within said  $N$  interference-reduced data signals.

11. (Original) The method of claim 10 wherein said determining is performed in a round robin manner relative to said  $N$  fingers.

12. (Original) The method of claim 9 wherein each of said  $N$  intra-finger interference cancellation signals is generated on the basis of one of said  $N$  interference-reduced data signals.

13. (Original) The method of claim 9 wherein said generating  $N$  intra-finger interference cancellation signals further includes creating at least  $N$  pilot channel models, each of said  $N$  pilot channel models being associated with one of said  $N$  fingers.

Appl. No. 10/649,335

Rule 312 Amdt. dated May 24, 2006

In Reply to Notice of Allowability of Feb. 24, 2006

14. (Previously Presented) A spread spectrum receiver comprising:

a rake receiver having N fingers for processing N data signals and N associated pilot signals, wherein N is an integer, each of said N fingers including an intra-finger interference cancellation module configured to generate an intra-finger interference cancellation signal using at least one of said N associated pilot signals; and

an inter-finger interference cancellation module for synthesizing N inter-finger interference cancellation signals, each of said N inter-finger interference cancellation signals being synthesized on the basis of a set of said intra-finger interference cancellation signals, said inter-finger interference cancellation module including:

a gain adjustment unit for weighting said intra-finger interference cancellation signals so as to generate a plurality of weighted intra-finger interference cancellation signals, and

a summation unit adapted to combine ones of said plurality of weighted intra-finger interference cancellation signals.

15. (Previously Presented) The receiver of claim 14 wherein each of said intra-finger interference cancellation modules includes a subtraction unit to which is applied one of said N inter-finger interference cancellation signals and one of said N data signals, thereby yielding N interference-reduced data signals.

16. (Previously Presented) The receiver of claim 15 wherein each of said intra-finger interference cancellation modules includes a pilot channel processing module configured to create a pilot channel model, each of said intra-finger interference cancellation signals being generated in accordance with one said pilot channel model and one of said N interference-reduced data signals.

17. (Original) The receiver of claim 15 wherein said inter-finger interference

Appl. No. 10/649,335

Rule 312 Amdt. dated May 24, 2006

In Reply to Notice of Allowability of Feb. 24, 2006

cancellation module further includes an interference cancellation verification unit adapted to determine interference levels remaining within said N interference-reduced data signals.

18. (Original) The receiver of claim 17 wherein said interference cancellation verification unit is disposed to determine said interference levels in a round robin manner relative to said N fingers.

19. (Previously Presented) The receiver of claim 17 wherein said interference cancellation verification unit is configured to identify ones of said N pilot signals interfering with reception of said N data signals within ones of said N fingers.

20. (Previously Presented) The method of claim 1 further including identifying ones of said plurality of pilot signals interfering with reception of said plurality of data signals within ones of said plurality of fingers.